



PREVOST

THE ULTIMATE EXPERIENCE

X3-45 VIP ENTERTAINER

- Low center of gravity for excellent driveability
- Abundant under floor storage and custom conversion space
- Exceptional handling with an independent suspension system
- PrevoSt unique power management system increases battery life and vehicle's power usage
- Integral stainless steel structure for optimal passenger safety
- PrevoSt Electronic Stability Program provides improved stability in adverse conditions
- Environmentally friendly Volvo D13 engine exceeds EPA emission regulations for clean air and fuel economy

SPECIFICATION HIGHLIGHTS

X3-45 VIP ENTERTAINER

USA

California - Bay Area

Tel: (510) 745-7515

California - Southern

Tel: 1-800-421-9958

Florida - Jacksonville

Tel: 1-800-874-7740

Florida - Orlando

Tel: 1-407-554-0196

Illinois - Chicago

Tel: (847) 778-7475

New Jersey - South Plainfield

Tel: 1-800-223-0830

Tennessee - Nashville

Tel: 1-877-299-8881

Texas - Fort Worth

Tel: 1-866-773-8678

Texas - Houston

Tel: 1-877-602-0273

Prevost USA Parts Customer Service

Tel Eastern Region: 1-877-279-1224

Tel Central Region: 1-877-279-1245

Tel Western Region: 1-877-279-1219

Canada

Alberta - Calgary

Tel: 1-833-644-6294

Alberta - Ft McMurray

Tel: 1-780-713-0274

British Columbia - Richmond

Tel: 1-604-940-3306

Ontario - Mississauga

Tel: 1-905-738-0881

Quebec - Lévis

Tel: 1-866-870-2046

Quebec - Montreal

Tel: 1-514-882-8973

Prevost Canada Parts Customer Service

Tel: 1-800-463-8876

prevostcar.com



@PrevostCoach

@PrevostPromos

These specifications are based on the latest product information available at time of printing (05/19) and are subject to change. Contact your Prevost Sales Manager for full details on standard features, packages and options available on the latest model.

GENERAL

| | |
|--|--|
| Length, Overall (ft) | 45 |
| Wheelbase (in) | 334.5 |
| Width, Overall (in) | 102 |
| Height, Overall (in) | 143.625 |
| Floor-to-ceiling Height (in) | 91.5 |
| Cabin Floor Height (in) | 49 |
| Underfloor Storage (w/ driver A/C) (cu. ft.) | 433 |
| Underfloor Compartment Doors Width (in) | 70.6 |
| Entrance Door Width (in) | 30.25 |
| Step Height (in) | 7" inside entrance steps 9 3/8" for the first step from the ground when kneeled |
| Ground Clearance (in) | 11 |
| Overhang (incl. bumper) - Front (in) | 72.25 |
| Overhang (incl. bumper) - Rear (in) | 86.6 |
| Turning Radius (ft) | 43.3 |
| Body Construction (structure) | Integral (Stainless/Rust Protected Mild Steel) |
| Body Construction | Luggage doors: Ribbed stainless steel |
| Body Construction (Sub-Frame) | Low-Alloy/High Tensile Steel |

| | |
|---|--------------------------|
| State-of-the-art Soundproofing | Standard |
| Fuel Tank (US gallons) | 203 |
| Fuel Filler Necks on Both Sides | Standard |
| Diesel Exhaust Fluid (DEF) Filler on Driver's Side | Standard |
| Gross Vehicle Weight Rating (lb/kg) | 55,000/25,174 |
| Axle Design Load Capacity - Front (lb/kg) | 19,000/8,648 |
| Axle Design Load Capacity - Drive (lb/kg) | 22,500/10,205 |
| Axle Design Load Capacity - Tag (lb/kg) | 14,000/6,350 |
| Wet Weight, w/ Driver A/C (lb/kg) | 30,540/13,853 |
| Wet Weight, w/ Full A/C (lb/kg) | 30,850/14,023 |
| Driver-only A/C | Standard |
| Full A/C | Optional |
| A/C Condenser w/ Copper Fins | Standard with full A/C |
| A/C Refrigerant | 134A |
| Cooling Capacity/Full A/C | 108,000 btu/hr or 9 tons |
| Two-Year Warranty | Standard |
| Five-Year Extended Warranty (engine & transmission) | Standard |

TIRES AND WHEELS

| | |
|--|----------|
| Michelin 315/80R22.5 (drive axle) | Standard |
| Michelin 365/70R22.5 (front and tag axles) | Standard |
| Aluminum Wheels 22.5 x 9 in. (drive axle) | Standard |
| Aluminum Wheels 22.5 x 10.5 in. (front and tag axles) | Standard |
| Dura-Bright Coating (aluminum wheels) | Optional |
| Michelin 455/55R22.5 Super Single Tires w/ 14" Wheels (drive axle) | Optional |

POWERTRAIN

| | |
|---|----------|
| EPA Compliant Volvo D13 Engine 500HP w/ Diesel Particulate Filter (DPF) and Selective Catalytic Reduction (SCR) | Standard |
| Engine Torque Rating (ft.-lb.) | 1750 |
| Allison 6 speed Automatic Transmission | Standard |
| Allison Hydraulic Transmission Retarder | Optional |
| Cruise Control | Standard |
| Engine Brake (on all cylinders) | Optional |
| Pneumatic Drive Belts Tensioners | Standard |
| Turbo-boost Gauge | Standard |
| Electric Air Intake Preheater | Standard |
| Prevost Exclusive - Electric engine Cooling Package | Standard |
| Coolant System w/ Recovery Tank | Standard |
| Engine Coolant Filter | Standard |
| Two-step Dual Filter w/ Water Separator | Standard |
| Prevost Liaison - 1 Year Coverage | Standard |
| Engine Maintenance Software w/ Laptop | Optional |
| Driver Electronic Message Center Display | Standard |
| Fuel Pro 382 Fuel Filter | Optional |

BRAKES

| | |
|-------------------------------------|------------|
| All-disc Brakes w/ ABS | Standard |
| Front Wheels Brake Boosters | Type 27 |
| Driver Wheels Brake Boosters | Type 24-24 |
| Tag Wheels Brake Boosters | Type 20 |
| Parking Brake Booster on Tag Wheels | Standard |

STEERING AND SUSPENSION

| | |
|---|----------|
| Tilt and Telescopic Steering Wheel | Standard |
| Bosch Constant Assistance Power Steering System | Standard |
| Bosch Variable Assistance Power Steering System | Optional |
| Independent Suspension System | Standard |
| Front and Drive Axle Sway Bars | Standard |
| Integrated Pneumatic Level-Low Leveling System | Standard |
| Liftable Tag Axle | Standard |

ELECTRICAL SYSTEM

| | |
|---|----------|
| Fully Multiplexed Electrical System | Standard |
| 12-volt Exterior Lighting | Standard |
| 24-volt Main System | Standard |
| Additional Alternator Configurations For Conversion | Optional |
| 4 AGM Batteries | Standard |
| Energy Management System | Standard |

INNOVATIVE SAFETY FEATURES

| | |
|--|----------|
| Prevost Electronic Stability Program | Standard |
| Prevost Aware - Adaptive Cruise and Collision Warning System | Optional |
| Automatic Fire Suppression System | Standard |
| Tire Pressure Monitoring System | Standard |
| Xenon Headlights | Standard |

FACTORY-INSTALLED EQUIPMENT

| | |
|--|------------------|
| Patented Prevost BEAM Frame Reinforcement For Factory Installed Slide-Outs | Standard |
| Factory Slide-Outs (electrical motors & pneumatic seals w/ aluminum frames) | Optional |
| Front Slide Driver's Side (interior dimensions) | 140" x 24" x 78" |
| Choice of Side Window Arrangement & Type Fixed, Electrical Awning or Sliding | Optional |
| LED Fog Lights | Standard |
| Driver's Window Blind | Optional |
| Left/Right Windshield Manual Blind | Standard |
| Electric Windshield Blinds LH and RH | Optional |
| Ramco Remote Heated Rearview Mirrors w/ Separate Convex Top (painted in black) | Standard |
| w/ Separate Convex Top (chromed) | Optional |
| Signal Mirrors w/ LED Light | Optional |
| Keyless Keypad w/ Multi-Code Capability | Standard |
| Central Electrical Door Locking System | Standard |
| Remote and Keyless Locking (entrance door) | Standard |
| Remote and Keyless Locking (compartment door) | Standard |
| Trailer Hitch Package (20,000 lb) | Standard |
| Trailer Air Brake Connection | Optional |
| Low Fuel Warning Light | Standard |
| Courtesy Lights Blinker Switch | Standard |
| Engine and Compartment Lighting | Standard |
| ISRI 6832 3 pt Seat Belt Air Ride Seat | Optional |
| ISRI 6832 Climate Control (heater and air circulation) | Optional |
| Exterior Graphic Design Assistance | Optional |
| Factory Exterior Paint w/ Special Effect | Optional |
| Back-up Sound Alarm | Standard |
| Headlamp Cleaning System | Standard |
| Emergency Escape Hatches | Optional |